

Fullmaster 10W-30

*Synthetic Based Effective Protection for
Diesel Engine*



PRODUCT DESCRIPTION

Fullmaster 10W-30, is a synthetic based engine oil which is developed to meet high performance requirements of light commercial vehicles.

APPLICATIONS

- It is suitable to use in diesel engines of light commercial vehicles.
- It is suitable to be use in Ford Transit vehicles manufactured in 2007 and before.

CHARACTERISTICS

- Its high viscosity index provides engine to function properly.
- Helps to protect against the build up of piston deposits for continuing engine efficiency
- Its high oxidation stability maintains its protect until the next oil change.

PERFORMANCES

- API CH-4
- FORD WSS-M2C921-A

TYPICAL PROPERTIES

Density@15°C, g/ml	ASTM D 4052	0,874
Viscosity@ 40°C, mm ² /s	ASTM D 445	75,1
Viscosity@100°C, mm ² /s	ASTM D 445	11,3
Viscosity Index	ASTM D 2270	143
Flash Point, °C	ASTM D 92	228
Pour Point, °C	ASTM D 97	-27
TBN, mgKOH/g	ASTM D 2896	11,6

HEALTH AND SAFETY RECOMMENDATIONS

Waste oils must not be discharged into underground or surface water sources, sewage systems or garbage cans. Prolonged or repeated contact with used oils may cause skin diseases. Therefore sterilized gloves should always be used. If part of the skin comes into contact with waste oil, that part should be immediately washed with plenty of soap and water. In case of skin irritation or redness caused by contact, seek advice of your doctor immediately. For more information contact Material Safety Data Sheet (MSDS).

The vehicle and equipment manufacturers specifications and relevant international standards were taken into consideration while preparing the content of this Technical Data Sheet. The expressions in the content of this Technical Data Sheet can not be considered as guarantee commitment or similar way in terms of product characteristics and product use in any applications.

The correct use of this product, compliance with applicable laws and regulations is responsibility of the user. Opet Fuchs Madeni Yağ. San. ve Tic. A.Ş. can not be held responsible for any loss or damage arising from the abnormal use and misuse or any hazards of product content and its results.

This Technical Data Sheet is valid from the date of publication. The information in the content of this Technical Data Sheet are subject to change without notice. Please contact with Opet Fuchs Technical Services Department for more information.